



15
15 year guarantee

KNURLED ACCENTS

NEW



A story of bold contrast, Knurled Accents fuses soft and organic brassware with striking, textured controls that awaken the senses through the power of touch.

Finished in crisp chrome the collection exudes style sophistication for those looking to create a unique statement with their brassware.

- ORI-200/CC-CPK
- ORI-209S/A-CPK
- TAB-128/3-H-CPK
- TAB-148/2-CPK



KNURLED ACCENTS.





BASIN MIXERS.



NEW

Mono
Basin Mixer
+ Universal Waste
ORI-200/CC-CPK



NEW

Wall Mounted
Basin Mixer

MP

ORI-209S/A-CPK

LP



Knurled details add a textured touch to our elegant Origins basin mixers creating a rich and alluring feature that will stand the test of time.

LP (0.2 bar) Minimum Operating Pressure

MP (1.0 bar) Minimum Operating Pressure

SHOWERING.

The intricate detailing of Knurled Accents combined with ergonomic soft-turn handles create a luxurious, sensory experience.



NEW

Tablet 3 Outlet
Thermostatic Valve
All-Flow

TAB-128/3-H-CPK

LP



NEW

Tablet 2 Outlet
Thermostatic Valve
All-Flow

TAB-148/2-CPK

LP



SPECIFICATIONS 2020




Knurled Accents

KNURLED ACCENTS

NEW



NEW




slimline Knurled Accents mono basin mixer
single lever, deck mounted, smooth bodied
with universal basin waste
with water flow aerator
ceramic cartridge C-010-N25
2 x 1/2" nut x 400mm flexipipe connections
deck mount drill hole diameter 35mm
minimum operating pressure 1.0 bar MP

chrome
ORI-200/CC-CPK

5 l/m flow regulator fitted as standard

NEW




slimline Knurled Accents mono basin mixer
single lever, deck mounted, smooth bodied
without universal basin waste
with water flow aerator
ceramic cartridge C-010-N25
2 x 1/2" nut x 400mm flexipipe connections
deck mount drill hole diameter 35mm
minimum operating pressure 1.0 bar MP

chrome
ORI-200/SB-CPK

5 l/m flow regulator fitted as standard

NEW




slimline Knurled Accents 2 hole basin mixer
single lever, wall mounted with water flow aerator
ceramic cartridge CAR-K35B
2 x 1/2" inlets
min-max wall mount 55-72mm
tile-to mortar guard included
wall mount drill hole diameters:
spout 40-48mm handle 45-48mm
minimum operating pressure 0.2 bar LP
when installing below 1.0 bar pressure, removal
of the flow regulator is required

chrome
ORI-209S/A-CPK

5 l/m flow regulator fitted as standard

NEW




Tablet Knurled Accents 3 outlet 3 handle
horizontal concealed thermostatic shower valve
with all-flow function
thermostatic cartridge V-704-34S
diverter cartridge FL-802-33/ZMX
flow cartridge TAB-002A-3/4
2 x 3/4" female inlets / 3 x 3/4" female outlets
includes 3/4" - 1/2" adaptors
supplied with mortar/tile guard
min-max wall mount 75-100mm
optimum installation depth 87mm
MOP - 0.2 bar LP (shower) 1.0 bar MP (bath)

chrome
TAB-128/3-H-CPK



NEW



Tablet Knurled Accents 2 outlet 2 handle
vertical concealed thermostatic shower valve
with all-flow function
thermostatic cartridge V-704-34S
diverter cartridge FL-802-33/ZMX
2 x 3/4" female inlets / 2 x 3/4" female outlets
includes 3/4" - 1/2" adaptors
supplied with mortar/tile guard
min-max wall mount 75-100mm
optimum installation depth 87mm
MOP - 0.2 bar LP (shower) 1.0 bar MP (bath)

chrome
TAB-148/2-CPK



WHERE INSPIRATION FLOWS



VADO
Wedmore Road Cheddar Somerset England BS27 3EB
tel +44 (0)1934 745160
fax +44 (0)1934 745161
www.vado.com
export@vado.com

due to our policy of continual improvement, VADO reserve the right to change product specification.
the colours indicated are an approximation of the actual finishes on VADO products. e&oe.
©2020 VADO LIT-VADO/EXKNU-AC20



The mark of
responsible forestry

